

Quill CONDOR ELECTRA



ALL ELECTRIC HOT STATIC PRESSURE WASHER

- Professional electrically heated pressure washer
- Outstanding heat retention
- First class engineering with full stainless steel sub frame
- CE Approved
- ISO9000



KEY SPECIFICATION

- 80°C Max Heat
- 11ltr, 13ltr or 15ltr/min Water Flow
- 18kW to 48kW Heating Power
- 120bar - 200bar Pressure
- 415v Power Supply

Quill CONDOR ELECTRA



STANDARD FEATURES

- Low revving 1450rpm pump & motor
- High pressure interpump
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Low thermal loss in standby
- Maximum temperature output 80°C
- Digital temperature display
- Simple 24v controls
- Available from 18kW to 48kW

CABINET FINISH

- Available in powder coated or stainless steel

OPTIONAL ACCESSORIES

- Remote control box
- Coin / token acceptor
- Lance & lance holder
- Key fob system

	ELECTRA 1	ELECTRA 2	ELECTRA 3	ELECTRA 4
Water Flow	13lt per minute	11lt per minute	13lt per minute	13lt per minute
Pressure	170bar	120bar	170bar	170bar
Motor Specification	5.5kW, 7.5hp, 1450rpm	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	24kW	18kW	36kW	48kW
Shutdown System	Timed total stop	Timed total stop	Timed total stop	Timed total stop
Max Temperature	80°C	80°C	80°C	80°C
Volts Amps Watts	415v / 45A / 29.5kW	415v / 32A / 22kW	415v / 60A / 41.5kW	415v / 80A / 53.5kW
Weight	250kg	250kg	250kg	250kg
Dimensions (h x w x d)	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm